



CHEMICAL DESIGN CORPORATION

906 H D Atha Road ♦ Monroe, Georgia 30655
Phone: 800-578-8555 ♦ Fax: 770-207-4535

CHEMICAL DESIGN BEDLINER PRODUCTS AND QWIK SPRAY SYSTEM Frequently Asked Questions

- **What is Qwik Spray System?**
Chemical Design offers two specifically formulated bedliner products to be used specifically with our Qwik Spray System. You can spray apply professional quality bedliners without investing all the money for expensive machinery. Chem-Coat 9-544-1 is a 100% solids, two-component polyurea aromatic coating available in black. Chem-Coat 9-344-1 is an aliphatic polyurea, 100% solids, two component coating available in several colors.
- **What are the benefits of using Qwik Spray Bedliner?**
The Qwik Spray System will increase your productivity while significantly reducing the labor costs associated with set-up and clean-up. The portability of the Qwik Spray System will increase business by allowing you to spray at alternate sites. The spray system will also provide excellent speed of application, control of your film thickness and transfer efficiency resulting in minimal material waste.
- **What colors are available?**
Chem-Coat 9-344-1 is available in six colors; white, dark grey, red, brown, green and blue. Chem-Coat 9-544-1 is available in black.
- **Are Chemical Design Bedliner products VOC friendly?**
These products are environmentally safe and contain no VOC's.
- **How is the Qwik Spray Bedliner packaged?**
The Qwik Spray Bedliner products are sold in cases. Each case consists of 6 kits; each kit contains 1500 ml of material and a case will cover 100 sq. ft. with 38 mils of coating. Included with each kit is a static mixer with an air atomizing tip. Extra static mixers with an air atomizing tip can be purchased separately.
- **How thick should your material be applied?**
We recommend that you apply our Qwik Spray Bedliner at a minimum application thickness of 40 mils. Depending on the use of your vehicle, you can spray this product thinner or thicker if necessary.
- **How long does it take the Qwik Spray Bedliner to dry?**
At 72°F, the Qwik Spray Bedliner is dry to the touch within 2 hours.
- **How long before my customers can take delivery of their truck?**
Generally, within 3-4 hours. Please allow 24 hours for heavy duty use to allow the material to fully cure.
- **Is the Qwik Spray Bedliner material repairable?**
Yes, our Qwik Spray Bedliner can be repaired.
- **Will the Qwik Spray Bedliner withstand extreme temperatures?**
Yes, the Qwik Spray Bedliners are functional between -40°F – 230°F.

- What other applications can Qwik Spray Bedliner be used for?**
 Our Qwik Spray Bedliner can also be used on other applications. The following are examples of potential applications: Lift trucks, trailers, recreational vehicles, commercial and off-highway vehicles, under body coating, deck coatings, roof repair, and secondary containment. Our technical support team will be please to evaluate and provide detailed advice for your specific applications.
- Can Qwik Spray Bedliner be used as an undercoating?**
 The Qwik Spray Bedliner is ideal for undercoating once you have properly masked and taped the critical components under the vehicle. The spray system will allow control of your film thickness and transfer efficiency.
- What type of equipment is required to spray the Qwik Spray System?**
 Our Qwik Spray System runs off of a standard compressor capable of 10 to 12 CFM. For optimum performance the supply pressure must be greater than 100 PSI (6.8 bar) and less than 145 PSI (10 bar). Depending upon your local authorities, you may be required to use a spray booth. Check with your local authorities to verify if a spray booth is necessary.
- Does Chemical Design supply the Qwik Spray System?**
 Yes, Chemical Design supplies the complete equipment package, with includes the following components: dual cartridge spray gun, air atomizing spray control, static mixers and air atomizing tip.
- Where do I get replacement parts for the Qwik Spray System?**
 Chemical Design carries all replacement parts for the Qwik Spray System. Just call our Sales Department to place your order at 800-578-8555.
- Is technical support available?**
 Our Technical Support Team is available to answer all your technical questions concerning the Qwik Spray System and Spray Bedliner. Call Technical Support at 800-578-8555.
- Does Chemical Design require any franchising fees?**
 No, franchising fees are not required to purchase any of our products.

Corporate Office: 906 HD Atha Rd. Monroe, GA 30655 - (800) 578-8555 - (770) 207-4534 - Fax (770) 207-4535

This information and technical advice provided herein are believed to be reliable and accurate to the best knowledge of Chemical Design Corporation, as based on tests and should serve only as a recommendation. As the manufacturer, Chemical Design Corporation makes no representations or warranties of any kind, expressed or implied, including but not limited to all implied warranties of merchantability or fitness for use or a particular purpose for the product. Chemical Design Corporation makes no representations or warranties as to the results of the use of the product and assumes no obligation or liability in connection therewith. Chemical Design Corporation is not liable for any incidental or consequential damages of any sort from use of this product. The information provided herein is subject to change at anytime without notice. Information changes may include, but are not limited to, commercial and technical changes, changes in pricing, physical characteristics and packaging.